

3M 9502V+

Particulate Respirator N95

Standard Size / Headband

User Instructions

IMPORTANT: Keep these User Instructions for reference

GB2626-2006 KN95



⚠ WARNING

This respirator helps protect against certain particles. **Misuse can result in sickness or death.** For proper use, see supervisor or User Instructions on package or call 3M, 400-920-3595. For US, call 1-800-243-4630.

IMPORTANT

Before use, the wearer must read and understand these User Instructions. Keep these instructions for reference.

Use For

Particles such as those from grinding, sanding, sweeping, sawing, bagging or processing minerals, silica, coal, iron ore, heavy metal, flour, wood, pollen and certain other substances. Liquid or non-oil based particles from sprays that do not also emit oil aerosols or vapors. Metal fumes produced from welding, brazing, cutting and other operations involving heating of metals.

Do Not Use For

Do not use for gases and vapors, oil aerosols, or sandblasting; particulate concentrations that exceed either 10 times the occupational exposure limit or applicable government regulations, whichever is lower. This respirator does not supply oxygen. Do not use in atmospheres containing less than 19.5% oxygen.

For Use in China: Do not use for oil based particles. Do not use for particles in concentrations that exceed the maximum allowable concentration required by the applicable regulation and standard. The maximum allowable concentration is obtained by multiplying the Assigned Protection Factor (APF) provided by GB/T 18664 "Selection, Use and Maintenance of Respiratory Protective Equipment" and the permissible Occupational Exposure Limit (OEL) of the contaminant.

Use Limitations and Warnings

1. The wearer must first be trained in the proper use and fit tested before using this respirator.
2. Do not use this respirator when concentrations of contaminants are immediately dangerous to life or health.
3. Leave the contaminated area immediately if breathing becomes difficult, or dizziness or other distress occurs.
4. Discard and replace respirator if it becomes damaged or breathing resistance becomes excessive.
5. Inspect respirator before each use to ensure it is in good working condition. Examine all the respirator parts for signs of damage including the two straps and noseclip.
6. Do not alter, wash, abuse or misuse this respirator.
7. Do not use with beards or other facial hair or other conditions that prevent a good seal between the face and the sealing edge of the respirator.
8. Can be used up to the limits specified by applicable government regulations for this product.
9. Failure to follow all instructions and warnings on the use of this respirator and/or failure to wear this respirator during all times of exposure can reduce respirator effectiveness and may result in illness or permanent disability.
10. Make sure the respirator is not crushed or squeezed by an outside force, as this may result in the deformation and damage of the respirator. Especially pay more attention when the wearer is biking, running or conducting other activities.
11. Outside forces acting upon the noseclip on the respirator may result in injury to the wearer.

CAUTION: Care should be taken when using the equipment at low temperatures as excessive moisture may cause valves to freeze.

Storage Conditions and Shelf Life

Shelf life of unopened product is 5 years from date of manufacture when stored within temperature range of -20°C to +30°C and at less than 80% relative humidity.



Shelf life of unopened product is 5 years from date of manufacture.



Temperature Range: -20°C to +30°C



Maximum Relative Humidity: <80%

<80%

This respirator contains no components made from natural rubber latex.

Fitting Instructions

Must be followed each time respirator is worn.



1. Place the respirator against your face with the nosepiece across the bridge of your nose. Hold the respirator on your face and position the respirator under the chin.
2. Pull the top strap over your head resting it high at the top of your head.
3. Pull the bottom strap over your head position it around the neck, below the ear.
4. Place the fingertips of both hands at the top of the metal nosepiece. Mold the nosepiece to the shape of the nose bridge by pushing inwards while moving your fingertips down both sides of the nosepiece. Pinching the respirator nosepiece using only one hand may result in less effective respirator fit.
5. The seal of the respirator on the face should be checked by the wearer prior to entering the work area.
 - a) Cover the front of the respirator with both hands, being careful not to disturb the position of the respirator.
 - b) Exhale sharply. If air leaks around the nose bridge, readjust the nosepiece as described in step 4. If air leaks at the respirator edges, work the straps back along the side of your head. If you CANNOT achieve a proper seal, DO NOT enter the contaminated area. See your supervisor.
 - c) If no leakage is detected, then work may proceed.

It is very important to press the nosepiece firmly to the nose bridge to form a good seal.

3M China Co. Ltd

222 Tianlin Road

Shanghai China 200233

Tel: 86-21-2210 5335

Fax: 86-21-2210 5035

Website : <http://www.3M.com.cn/PPE>

Made in China

© 3M 2018. All rights reserved.

3M is a trademark of 3M Company.